



SHOTBLASTING MACHINE

1-8DPS30

TECHNICAL DATA	
Working width	203mm
Blasting capacity	Up to 50m ² /h on concrete
Motor	3,0kW / 230V - 50Hz or 60Hz / 16A - Single phase 3,0kW / 400V - 50Hz or 60Hz / 16A - Three phase - 5 pole
Weight	125 kg
Dimensions L / W / H	1.310mm / 400mm / 1.200mm
Drive system / Speed	Electric / 0 - 23 m/min
Push / Pull machine	Pull
Abrasive consumption	10 - 75 gr/m ²
Surface	Steel / Concrete / Stone / Asphalt

OPTIONS / ACCESSORIES	
Dustcollector	BDC-1330 / BDC-1330LP / BDC-1330LPP
Abrasive S330 / S390	999-0330 / 999-0390
10m suction hose Ø76	005014
Magnetic sweeper	489538
Magnetic broom R600	001238
Maintenance kit	E07007
Personal safety features	On request / See manual



BDC-1330



MAIN ASSETS

- Closed circuit which is dust free, when connected to an appropriate Blastrac dust collector.
- Universal unit: can be connected to a standard electrical plug (230V).
- First model of the range with an electric drive system.
- Ergonomic design and user's friendly control panel.
- Heavy duty professional equipment available either in 230V (easy to plug on every jobsite) or 400V.
- Reliable machine, suitable for rental.
- Easy to transport, handle and use.
- Can be used for floor preparation / renovation / maintenance and decorative purposes.

FOR MORE INFORMATION VISIT WWW.BLASTRAC.EU

Blastrac 06/2012 • This document is not contractual • Design and technical specifications may be subject to changes